Technical Data Sheet

n. 04 [November 2023]

Vibrational Shakers

COROB EVOshake 200

BASE FEATURES	
Type	Vibrational shaker
Clamping function	Automatic
Clamping force [kg]	Automatically selected [depends on can size]
Shaking time [min]	Manual set from 30 s to 20 m [up to 40 m with tech configuration]
Shaking speed [rpm]	680
Shaking motor power [hp] (kW)	0.75 (0.55)
Working cycle	Continuous
Shaking direction	One direction

VERSIONS	
Panels	Sheet Metal panels
Door type	Hinge door

CAN HANDLING FEATURES	
Type of cans	Round / Square / Oval
Minimum can height [mm] (in)	50 (2)
Maximum can height [mm] (in)	410 (16.1)
Maximum can diameter [mm] (in)	365 (14.4)
Maximum can weight [kg] (lbs)	35 (77)
Multiple can handling	Yes / 4 x 1G with cartonbox

POWER SUPPLY / MACHINE ENVIRONMENT	
Power supply [V]	Single phase; 200-240±10% [Option: 100-120V±10%]
Frequency [Hz]	50 [Option: 60]
Fuses	F 10 A
Maximum power absorption [W]	650
Working temperature [Celsius] (Fahrenheit)	From 10° to 40° (50° to 104°)
Relative humidity	From 5% to 85% (without condensation)
Noise level [dB(A)]	< 70
Certification	CE/UKCA (ETL certification during Q1\2024)

OVERALL DIMENSIONS	
Length [mm] (in)	616 (24.2)
Depth [mm] (in)	602 (23.7)
Height [mm] (in)	1132 (44.6)
Footprint [m^2] (ft^2)	0.37 (4)
Machine Weight [kg] (lbs)	185 (408)
Machine + packaging Weight [kg] (lbs)	210 (463)

Take note: data refers to base configuration machine, figures may vary according to different specifications. **The EVOshake 200 is the standard version not available for the US market. The EVOshake 200 [US] is the version for the US market with the same technical specifications and with a dedicated clamping system.**

© COPYRIGHT 2023, COROB S.p.A. - All rights reserved in all countries
This information is provided without warranty, representation, inducement or license of any kind. It is accurate to the best COROB's knowledge or is obtained from sources believed to be accurate. COROB therefore assumes no legal responsibility for reliance upon given information.